



Model: 12BST

| | | | |
|------------------|---------------------|------------------------|---------------------------------------|
| CAPACITY: | 12,000# @ 65 MPH | Main Rails: | W12" x 16" A572 Gr. 50 - High Tensile |
| Trailer Weight: | 4,575# | Crossmembers: | 6" Jr. I Beam - High Tensile |
| Overall Length: | 27' 3" | Heavy Duty Axles: | (2) "Dexter" 6,000# capacity |
| Overall Width: | 96"/102" | Heavy Duty Brakes: | Electric, 12" x 2" Each Wheel |
| Platform Length: | 20' 0" | Jack: | 5000# Screw Type |
| Platform Height: | 34" | Heavy Duty Suspension: | Spring Type |
| Dovetail Length: | 42" | Tires: | (4) 235/85R16, (E) |
| Ramp Length: | 54 1/2" | Heavy Duty Wheels: | 8 Hole, Steel Disc |
| Ramp Width: | 21 1/2" | Lights & Electric: | Sealed Beam System/ICC & DOT Approved |
| Decking: | 2" Nominal Hardwood | Hitch: | Adjustable Pintle Eye - 4 Position |

Gell Cell Break-A-Way Switch System with Battery

Your **INTERSTATE** Dealer Is